



## **K25 - MIX**

**HARD CHROME  
OVER STAINLESS  
STEEL CONSTRUCTION**

**DUAL AIR REGULATORS**

**25:1 RATIO AIR-  
LESS UNIT**



**HIGH DELIVERY  
RATE OF .5 GPM AT  
60 CYCLES**

**K1 MIX OR K1 3A  
MIX GUN WITH  
VARIOUS TIP SIZES**

**ADJUSTABLE  
SPRAY PRESSURE  
UP TO 2850 LBS**

**THE ATOMIZATION AIR IS BLENDED WITH FLUID AT THE TIP'S OUTLET  
ALLOWING A VERY STABLE AND EVEN SPRAY PATTERN, UNIFORM FILM  
BUILD AND SUPERIOR FINISHES WITH GREATER TRANSFER EFFICIENCY.  
COMBINES THE ADVANTAGES OF AIRLESS AND AIR SPRAYING.**

**HIGH SPEED OF APPLICATION AND FLUID DELIVERY WITH A SUPERIOR  
FINISH QUALITY**

**EXTREMELY EFFICIENT METHOD TO APPLY TOPCOATS**

- 142500smc**      **K 25 - MIX**      **Hard Chrome over stainless steel pneumatic piston pump with dual regulator (pump and gun air adjustment). Anodized pump body. Shut off air valve. Cart Mounted, Stainless steel wet parts and fittings. Fluid suction set for 5 gal. pail. Complete with K1 MIX Gun, tip, and 25' air and fluid hoses.**
- 142501smc**      **Same as above-on WALL MOUNTING BRACKET**
- 142501sm**      **UNIT ONLY - on WALL MOUNTING BRACKET**
- 142502 smc**      **Same as above - K1 3A MIX GUN (reversing tip for ease of tip-clog removal), CART MOUNTED**
- 142503 smc**      **Same as above - with K1 3A MIX GUN ON WALL MOUNTING BRACKET**



**K1 3A MIX GUN**



**K1 MIX GUN**

VOLUME PER CYCLE (CC) (OZ) 0.78	DELIVERY (I/MIN) (G.P.M.) 3 0.8	MAX. FLUID PRESSURE (BAR) (PSI) 200 2.850	MAX.AIR PRESSURE (BAR) (PSI) 8 115	WORKING PRESSURE (BAR) (PSI) 8 115	AIR CONSUMPTION (I/MIN) (C.F.M.) 190 6.65	WEIGHT (KG) (LB) 25 55
--	---	---	--	--	---	------------------------------------



**AOM SPRAY EQUIPMENT**  
 5005 SANBUSCO DR. NE  
 RIO RANCHO, NM 87144  
 505-867-1946 FAX: 505-867-1948  
 E-MAIL: AOMAMERICA@AOL.COM  
 HTTP: WWW.AOMSPRAY.COM