



K30

STAINLESS STEEL WET PARTS AND ANODIZED MOTOR BODY ALLOW APPLICATION OF VIRTUALLY ALL WATERBORNE COATINGS.

HEAVY DUTY CART WITH AN EASY-TO-REMOVE WALL MOUNTING BRACKET

TWO PARTS FLUID SECTION ALLOWING AN USER FRIENDLY ACCESS FOR SERVICING AND CLEANING



STATE OF THE ART AIR ASSISTED AIRLESS AND AIRLESS SPRAY GUNS AND REVERSIBLE TIPS

HARD CHROME OVER STAINLESS STEEL WEARING PARTS DURABILITY, HIGH PERFORMANCE, TROUBLE-FREE RELIABILITY, PRODUCTIVITY

30:1 RATIO AIRLESS UNIT, THANKS TO ITS HIGH DELIVERY IT IS EXCELLENT FOR MEDIUM AND LARGE SURFACE AREAS

AOM high pressure pumps are specifically designed for Airless and air assisted airless spraying of most conventional and waterborne materials, with the following advantages:

- High viscosity coatings with low-solvent content can be applied reducing Overspray.
- Environments friendly cleaner working conditions, 20-30% less VOC emissions when compared to conventional air spraying equipment.
- Increased shop productivity thanks to a faster drying time and a quicker speed of application, one coat can be sufficient in most cases.
- Maximize its advantages when used to apply high volumes of materials to medium and large surface areas.

Can operate multiple Airless guns simultaneously, either manual or automatics, depending on the tip size selected.

Cart or Wall mounted options, siphons directly from manufacturer's container. A 1.3 gal. gravity tank is available for small quantities.

Adjustable spraying pressure from 0 to 3,500 PSI, operates tips from 007" to 031" depending on the number of guns installed, hose length and viscosity of material being sprayed.

K30 Mix

143000mi 30:1 Dual Kinetic Pneumatic piston pump, **Hard chrome over stainless steel** with dual air line filter, regulator unit, stainless steel manifold filter with pulsation chamber, shut-off air valve, fluid drain valve, cart mounted. Anodized pump body, stainless steel wet parts and fittings, fluid suction set.

143001mi Same as above on WALL MOUNTING BRACKET

K30

143000i 30:1 Pneumatic piston pump, **Hard chrome over stainless steel** with air line filter, lubricator and single regulator unit, stainless steel manifold filter with pulsation chamber, shut-off air valve, fluid drain valve, cart mounted. Anodized pump body, stainless steel wet parts and fittings, fluid suction set.

143000ci Same as above but with K90 gun, 25' hose and flat tip

143001i Same as 143000i above but on WALL MOUNTING BRACKET

143001ci Same as above on Wall Mount complete with K90 gun, 25' hose and tip



**K90
Airless Gun**



**K1 MIX GUN
Air Assisted Airless Gun**

VOLUME PER CYCLE (CC) (OZ) 2	DELIVERY (L/MIN) (G.P.M.) 6.5 1.6	MAX. FLUID PRESSURE (BAR) (PSI) 240 3,500	MAX. AIR PRESSURE (BAR) (PSI) 8 115	WORKING PRESSURE (BAR) (PSI) 3-8 40-115	AIR CONSUMPTION (L/MIN) (C.F.M.) 840 29	WEIGHT (KG) (LB) 30 66



**A.O.M. SPRAY EQUIPMENT
5005 SANBUSCO DR. NE
RIO RANCHO, NM 87144
505-867-1946 FAX: 505-867-1948
HTTP: WWW.AOMSPRAY.COM**